


LMBKC



LMBFC

Shaft diameter d :

(Inch) : 3/8 9.525

(mm) : 9.525

Bearing number :

LMBFC YUU : LMBFC6UU

Weight (g) : 60

LMBKC YUU : LMBKC6UU

Weight (g) : 45

Inside diameter dr :

(Inch) : .3750

(mm) : 9.525

Inside diameter tolerance :

(Inch) : 0-.00040

(μ m) : 0 -10

Outer diameter D :

(Inch) : 0.6250

(mm) : 15.875

Inside diameter tolerance :

(Inch) : 0-.00065

(μ m) : 0 -16

Length L :

(Inch) : 1.5938

(mm) : 40.481

Length tolerance :

(Inch) : $\pm .012$

(μ m) : ± 300

Flange :

I (Inch) : 0.6719

I (mm) : 17.066

Df (Inch) : 1.5000

Df (mm) : 38.100

K (Inch) : 1.2500

K (mm) : 31.750

t (Inch) : .2500

t (mm) : 6.350

Dp (Inch) : 1.0620


Dp (mm) : 26.988

X (Inch) : .1875

X (mm) : 4.763

Y (Inch) : .2969

Y (mm) : 7.541



Z (Inch) : .1719

Z (mm) : 4.366

Eccentricity :

(Inch) : 0.0006

(μ m) : 15

Perpendicularity :

(Inch) : 0.0006

(μ m) : 15

Basic Load Rating (N) :

Dynamic C : 353

Static Co : 630

: