


LMBKC



LMBFC

Shaft diameter d :

(Inch) : 3/4 19.050

(mm) : 19.050

Bearing number :

LMBFC YUU : LMBFC12UU

Weight (g) : 280

LMBKC YUU : LMBKC12UU

Weight (g) : 240

Inside diameter dr :

(Inch) : .7500

(mm) : 19.050

Inside diameter tolerance :

(Inch) : 0-.00050

( $\mu$  m) : 0 -12

Outer diameter D :

(Inch) : 1.2500

(mm) : 31.750

Inside diameter tolerance :

(Inch) : 0-.00075

( $\mu$  m) : 0 -19

Length L :

(Inch) : 3.0937

(mm) : 78.581

Length tolerance :

(Inch) :  $\pm .012$

( $\mu$  m) :  $\pm 300$

Flange :

I (Inch) : 1.3906

I (mm) : 35.322

Df (Inch) : 2.1875

Df (mm) : 55.563

K (Inch) : 1.6875

K (mm) : 42.863

t (Inch) : .3125

t (mm) : 7.938

Dp (Inch) : 1.7180


Dp (mm) : 43.656

X (Inch) : .2188

X (mm) : 5.556

Y (Inch) : .3438

Y (mm) : 8.731



Z (Inch) : .2031

Z (mm) : 5.159

Eccentricity :

(Inch) : 0.0008

( μ m) : 20

Perpendicularity :

(Inch) : 0.0008

( μ m) : 20

Basic Load Rating (N) :

Dynamic C : 1370

Static Co : 2740

: