


LMBKC



LMBFC

Shaft diameter d :

(Inch) : 1.25400

(mm) : 24.400

Bearing number :

LMBFC YUU : LMBFC16UU

Weight (g) : 515

LMBKC YUU : LMBKC16UU

Weight (g) : 470

Inside diameter dr :

(Inch) : 1.0000

(mm) : 25.40

Inside diameter tolerance :

(Inch) : 0-.00050

(μ m) : 0-12

Outer diameter D :

(Inch) : 1.5625

(mm) : 39.688

Inside diameter tolerance :

(Inch) : 0-.00075

(μ m) : 0-19

Length L :

(Inch) : 4.2813

(mm) : 108.744

Length tolerance :

(Inch) : $\pm .012$

(μ m) : ± 300

Flange :

I (Inch) : 1.9844

I (mm) : 50.403

Df (Inch) : 2.2500

Df (mm) : 63.500

K (Inch) : 2.0000

K (mm) : 50.800

t (Inch) : .31257

t (mm) : 0.938

Dp (Inch) : 2.0310


Dp (mm) : 51.594

X (Inch) : .2188

X (mm) : 5.556

Y (Inch) : .3438

Y (mm) : 8.731



Z (Inch) : .2031

Z (mm) : 5.159

Eccentricity :

(Inch) : 0.0008

(μ m) : 20

Perpendicularity :

(Inch) : 0.0008

(μ m) : 20

Basic Load Rating (N) :

Dynamic C : 1570

Static Co : 3140

: